

UNITED STATES OF AMERICA
FEDERAL COMMUNICATIONS COMMISSION
AM BROADCAST STATION LICENSE

File No. : BL-950824AA

Call Sign : KBBK

LICENSEE: Tri-Market Radio Broadcasters, Inc.

1. Community of License . . . : Rupert, Idaho
2. Transmitter location : S.E. Corner, 300W, 100S,
Rupert, Idaho
North Latitude : 42° 36' 10"
West Longitude : 113° 43' 21"

3. Transmitter(s): Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's rules)
4. Main Studio Location: (See Section 73.1125)
S.E. Corner, 300W, 100S,
Rupert, Idaho
5. Remote control location

6. Antenna and ground system:
Attached

7. Obstruction marking and lighting specifications - FCC Form 715, paragraphs: 1, 3, 11, 21 & 22.

8. Frequency : 970 kHz

9. Nominal power (kW) : 2.5 Day 0.9 Night

Antenna input power (kW) :

2.5 Day Non-directional antenna: current 7.3 amperes: resistance 46.8 ohms.
 Directional antenna :
1.02 Night Non-directional antenna: current 4.52 amperes: resistance 50 ohms.
 Directional antenna :

10. Hours of operation : BP-861031AC, BMP-950517DC

11. Conditions : --

Subject to the provisions of the Communications Act of 1934, as amended, subsequent Acts, Treaties, and Commission rules made thereunder, and further subject to conditions set forth in this license,¹ the LICENSEE is hereby authorized to use and operate the radio transmitting apparatus herein described for the purpose of broadcasting for the term ending 3 A.M. Local Time
October 1, 1997

The Commission reserves the right during said license period of terminating this license or making effective any change, or modification of this license which may be necessary to comply with any decision of the Commission rendered as a result of any hearing held under the rules of the Commission prior to the commencement of this license period.
The license is issued on the licensee's representation that the statements contained in the licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.
This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934, as amended. This license is subject to the right of control by the Government of the United States conferred by section 606 of the Communications Act of 1934, as amended.

JAV:rao

FEDERAL
COMMUNICATIONS
COMMISSION



¹ This license consists of this page and pages 2 & 3

Dated: DEC 14 1995

**FCC Form 353-A
June 1980**

File No.: BL-950824AA

Call Sign: KBBK

1. DESCRIPTION OF DIRECTIONAL ANTENNA SYSTEM

No. and Type of Elements: Two (2) guyed, series-excited, steel radiators of uniform cross-section. Theoretical RMS: 286.91 mV/m/km. Standard RMS: 301.44 mV/m/km. Q factor: 10.0, Night.

Height above Insulators: 76.2 m (88.8°)

Overall Height: 77.4 m

Spacing and Orientation: Towers are spaced 200° apart on a line bearing 454° True.

Non-Directional Antenna: Tower #1(S) used daytime. Theoretical efficiency is 305.8° mV/m/km.

Ground System consists of 120 buried copper radials 77.4 m long.

2. THEORETICAL SPECIFICATIONS

	Tower	#1(S)	#2(N)
Phasing: Night:		0°	71°
Field Ratio:			
Night:		1.0	0.85

3. OPERATING SPECIFICATIONS

Phase Indication*:

Night:	0°	71.8°
--------	----	-------

Antenna Base

Current Ratio:

Night:	1.000	0.849
--------	-------	-------

Antenna Monitor

Sample Current Ratio:

Night:	1.000	0.850
--------	-------	-------

* As indicated by Potomac Instruments AM-19 (204) Antenna Monitor.
Antenna sampling system approved under Section 73.68 (b) of the Rules.

DESCRIPTION OF AND FIELD INTENSITY AT MONITORING POINTS:

Direction of 50° True North. From the KBBK parking lot, proceed North on 300 West Road approximately 3.5 km to 100 North Road. Proceed East on 100 North Road approximately 4.65 km to Meridian Road. Proceed North on Meridian approximately 0.25 km to the intersection of Meridian and 120 North Road. The monitor point is located on the North-east corner, approximately 1.5 Meters South of Stop sign. The field intensity measured at this point should not exceed 7.9 mV/m.

Direction of 173° True North. From the KBBK parking lot proceed South on 300 West Road approximately 1.4 km to 200 South Road. Proceed East on 200 South Road approximately 200 West Road. Proceed South on 200 West Road approximately 4.55 km to 400 South Road. Proceed West on 400 South Road approximately 1.1 km to monitoring point. The monitoring point is located on the south shoulder of the road in line with a fence line to the South. The fence is located approximately 60 Meters West of a house on the South side of the road. The field intensity measured at this point should not exceed 40.7 mV/m.

Direction of 296° True North. From the KBBK parking lot proceed North on 300 West Road approximately 1.85 km to Baseline Road. Proceed West on Baseline Road approximately 4.8 km to 600 West Road. Proceed North on 600 West Road approximately 0.83 km to dirt field road to the West. Proceed West on field road approximately 0.4 km to jog to the right in the field road. The monitor point is located approximately 9 Meters East and 6 Meters South of pipe placed on North side of the road just West of jog. The field intensity measured at this point should not exceed 5.9 mV/m.